



Fluting

TİPİK DEĞERLER

TEST	Metot	Birim	FLUTING									
Gramaj	T410	g/m ²	80	85	90	100	112	125	135	140	175	
Rutubet	T412	%	8,0	8,0	7,9	8,0	8,0	8,0	8,0	8,1	8,0	
SCT CD	T826	kN/m	1,20	1,28	1,35	1,57	1,77	1,88	2,03	2,06	2,54	
SCT CD indeksi	T826	kN.m/kg	15,0	15,1	15,0	15,7	15,8	15,0	15,0	14,7	14,5	

GARANTİ EDİLEN DEĞERLER

TEST	Metot	Birim	Tolerans	FLUTING									
Gramaj	T410	g/m ²	% ± 4	80	85	90	100	112	125	135	140	175	
Rutubet	T412	%	± 1,5	8,5	8,5	8,5	8,5	8,0	8,0	8,0	8,0	8,0	
SCT CD	T826	kN/m	min	1,10	1,20	1,30	1,35	1,45	1,65	1,78	1,85	2,40	
SCT CD indeks	T826	kN.m/kg	min	13,8	14,1	14,4	13,5	12,9	13,2	13,2	13,2	13,7	

Test Şartları 23±1°C, 50% ± 2% RH

ISO 9001:2015
ISO 14001:2015
ISO 45001:2018
ISO 50001:2018
TS 12728



The mark of responsible forestry



*Kuru, yağlı olmayan, soyulabilir, yıkanabilir gıdalar ile temasa uygundur.
İşletme Kayıt No:TR-59-K-016501