



Beyaztestliner

TİPİK DEĞERLER

TEST	Metot	Birim	BEYAZ TESTLINER			
Gramaj	T 410	g/m ²	115	120	125	140
Rutubet	T 412	%	8,0	8,0	8,0	8,0
SCT CD	T 826	kN/m	1,50	1,8	1,87	2,07
SCT CD indeksi	T 826	kN.m/kg	13,0	15	14,9	14,8
Patlama	T 403	kPa	205	249	255	283
Cobb60 üst	T 441	g/m ²	35	35	35	35
Bendtsen Roughness	ISO 8791-2	ml/dak	500	500	500	500
Brightness	T 525	%	69	69	69	69

GARANTİ EDİLEN DEĞERLER

TEST	Metot	Birim	Tolerans	BEYAZ TESTLINER			
Gramaj	T 410	g/m ²	% ± 4	115	120	125	140
Rutubet	T 412	%	± 1,5	8,0	8,0	8,0	8,0
SCT CD	T 826	kN/m	min	1,40	1,49	1,55	1,70
SCT CD indeksi	T 826	kN.m/kg	min	12,2	12,4	12,4	12,1
Patlama	T 403	kPa	min	190	202	210	230
Cobb60 üst	T 441	g/m ²	± 15	40	40	40	40
Bendtsen Roughness	ISO 8791-2	ml/dak	max	750	750	750	750
Brightness	T 525	%	min	65	65	65	65

Test Şartları 23±1°C, 50% ± 2% RH

ISO 9001:2015
ISO 14001:2015
ISO 45001:2018
ISO 50001:2018
TS 12728



*Kuru, yağlı olmayan, soyulabilir, yıkanabilir gıdalar ile temasa uygundur.
İşletme Kayıt No:TR-59-K-016501